

Disintegration Test Apparatus



Disintegration Test Apparatus
2 Basket



Disintegration Test Apparatus

Disintegration Test Apparatus

Model : DT2025+

Low noise Double Basket Apparatus (1 + 1 Separate Operate)

B.P / USP Specifications. Precise temperature control with
5" Color Touch Screen controlled through built in microprocessor

Equipped with digital Lab. Counter / Stop watch.

Water Circulatory system in water bath to ensure uniform temperature.

21 CFR Part II Compliance

Precise temperature control with set point changing light through built in microprocessor
($\pm 0.3^{\circ}\text{C}$)

Print out Data & Data Storage logger. Operating User Password.

Method System Data Entry (products name , batch number, operator ID, QC/QA)

SPECIFICATION:

PARAMETER	Model DT-2025+ Double	Model DT2025+ Single
LCD Size	5" Inch	68 x 128 Graphic LCD
Screen Type	HDMI Touch Screen	Key Pad Operator
RPM Range	30 RPM	30 RPM
Motor Type	Double Stepper Motor (1 x) 1	SingleDC Motor
Temp. Range	32 C – 40 C	32 C – 40 C
Temp. Accuracy	+0.5 C	+0.5 C
Water Circulation	YES	YES
Heater Power	800 W	800 W
Over Heating Protection	YES	NO
Report Memory	500 Test	--
Printer Interface	Thermal Printer (Built in)	--
Water Tank	Molded Acrylic	Molded Acrylic
System Login Security	Operator ID Security	--
Dimension (CM)	45 x 35 x 50(LxWxH)	45 x 35 x 50(LxWxH)
Weight (Kg)	15	12
Max. Power	1000 W (approx)	1000 W (approx)